

The Power of Experience



Penn Yan Aero  
2469 Bath Road  
Penn Yan, New York 14627

800-727-7230 / 315-536-2333  
Fax: 315-536-2335  
www.PennYanAero.com

• FAA Approved Repair Station Number: Y2GR296Y • Authorized Textron Lycoming, Teledyne Continental, & ECI Distributor • Superior Mellenium Engine Facility

FAA APPROVED SUPPLEMENT  
TO THE  
PILOT'S OPERATING HANDBOOK AND  
FAA APPROVED AIRPLANE FLIGHT MANUAL

FOR

CESSNA MODELS 172N or P

REG. NO. N6506D

SER. NO. 17272835

This Supplement must be attached to the "Pilot's Operating Handbook and FAA Approved Airplane Flight Manual when the aircraft is modified by the installation of a 180 HP engine and the gross weight is increased in accordance with STC SA703GL. The information contained herein supplements or supersedes the basic manual only in those areas listed. For limitations, procedures and performance information not contained in this Supplement, consult the basic "Pilot's Operating Handbook and FAA Approved Airplane Flight Manual."

FAA APPROVED:

FOR

*W. F. Horn*  
W. F. Horn, Manager  
Chicago Aircraft  
Certification Office  
FAA Central Region

DATE: June 11, 1985

Page 1 of 4

PENN YAN AERO SERVICE INC.  
 FAA APPROVED  
 AIRPLANE FLIGHT MANUAL SUPPLEMENT  
 FOR CESSNA 172 SERIES AIRCRAFT

<u>LOG OF REVISIONS</u>				
<u>Rev. No.</u>	<u>Page No.</u>	<u>Description</u>	<u>FAA Approved</u>	<u>Date</u>
A	4	Added performance information to Section 5 for clarification.		
		Added Log of Revisions Page 2	<i>J. Brumer</i>	3/8/94
		Renumbered pages	Irwin N. Brumer Manager, NYACO	

Penn Yan Aero Service, Inc.  
2499 Bath Road, Airport  
Penn Yan, NY 14527-9599

POH and AFM Supplement  
for Cessna 172N and P

SECTION I - General

DESCRIPTIVE DATA

A. Engine

Number of engines: 1  
Engine Manufacturer: Avco Lycoming  
Engine Model: O-360-A4A, -A4M, -A4N  
Horsepower Rating and Speed: 180 rated BHP at 2700 RPM

B. Propeller

Propeller Manufacturer: Sensenich  
Propeller Model Number: 76EM8S5 or 76EM8SPY  
Number of Blades: 2  
Propeller Diameter: 76 inches  
Propeller Type: Fixed Pitch

SECTION II - Limitations

A. The following placard must be displayed in full view of the pilot:

THIS AIRCRAFT HAS BEEN MODIFIED BY THE INSTALLATION OF A 180 HP  
ENGINE PER STC SA703GL. IT MUST BE OPERATED AS A NORMAL CATEGORY  
AIRPLANE IN COMPLIANCE WITH THE OPERATING LIMITATIONS AS STATED  
IN THE FORM OF PLACARDS, MARKINGS AND MANUALS.

B. For the N model aircraft the following placard must be displayed  
adjacent to the flap position selector switch:

MAXIMUM FLAP TRAVEL IS 30°

C. The following limits apply to the normal category only.

Maximum Gross Weight - 2550 lbs.  
C.G. Range - 41.0" to 47.3" at 2550 lbs.  
35.0" to 47.3" at 1950 lbs. or less  
Straight line variation between points given.

FAA APPROVED  
DATED:     JUN 11 1985    

Page 3 of 4

Section 3      Emergency Procedures  
NO CHANGE

Section 4      Normal Procedures  
NO CHANGE

Section 5      Performance  
Performance of the Cessna 172 series aircraft, when it is modified by the installation of a 180 HP engine and the gross weight is increased, in accordance with STC SA703GL, will be equal to or better than the basic airplane

CAUTION: -      The fuel consumption and range/endurance information originally presented for this model do not apply to this STC modification; increased fuel consumption and reduced range/endurance can be expected with the 180 hp engine installed.

FAA APPROVED  
DATE:  
Revised: APR 13 1984

Page 4 Of 4

CURVE NO. 13357

